VOLUME 02 ISSUE 11 Pages: 119-126

SJIF IMPACT FACTOR (2021: 5.478) (2022: 5.636)

METADATA IF - 7.356

















Website: Journal http://sciencebring.co m/index.php/ijasr

Copyright: Original content from this work may be used under the terms of the creative commons attributes 4.0 licence.



Research Article

NOMOGRAM FOR DETERMINING THE PERFORMANCE PARAMETERS OF THE PRE-SEEDING LEVELER

Submission Date: November 05, 2022, Accepted Date: November 15, 2022,

Published Date: November 30, 2022

Crossref doi: https://doi.org/10.37547/ijasr-02-11-18

Kamaljon Jamalovich Mukhamadsadikov

Candidate Of Technical Sciences, Associate Professor, Fergana Polytechnic Institute, Fergana, Republic Of Uzbekistan

Bobojon Saparali O'g'li Ortiqaliyev

Assistant, Fergana Polytechnic Institute, Fergana, Republic Of Uzbekistan

ABSTRACT

The article describes the results of research on determining the technical parameters of the pre-sewing land leveling machine on case of the wide o working and working speed.

KEYWORDS

Pre-sewing leveling, land leveling machine ide and speed determination, diagram of its interdependence.

Introduction

The speed of agricultural machines is determined primarily based on the requirements of the existing technological process. Some processes require slow spreading of the aggregate mass into the soil (or compaction). In this case, the unit with a large weight should move at a low speed. In other cases, especially when leveling the land

before planting, a minimum level of soil compaction is required, because the soil density increases as a result of the aggregate entering the field many times in one cycle of agricultural crops. In order to prevent such an adverse situation, it is necessary to reduce the contact time between soil

VOLUME 02 ISSUE 11 Pages: 119-126

SJIF IMPACT FACTOR (2021: 5.478) (2022: 5.636)

METADATA IF - 7.356















and aggregate. This is done by increasing the working speed of the aggregates [1-4].

RESEARCH METHODS

The performance of agricultural aggregates can be determined by their coverage width and speed of movement or engine power and specific resistance of the aggregate:

(1)

$$W = 0.1BV$$

$$W = \frac{27N_e}{K} \varepsilon_{N_e} \eta_{mp} \tag{2}$$

W= unit's hourly productivity ha\h;

B= coverage width of aggregate, m;

Ne = effective power of the engine, kW;

V= working speed of the unit, m\s;

Kv= specific resistance of aggregate, N\m;

 ε_{N_e} = engine effective power utilization coefficient;

 $\eta_{\rm TD}$ = useful tractor efficiency.

The sweep width B is a function of a number of uncorrelated variables and the speed of movement.

$$B = F (KvNe\eta_{mp}V)$$
 (3)

The relative resistance Kv, which depends on the speed of movement of the rectifier, is a factor affecting the coverage width and speed of movement of the unit [5-9]. The relative resistance of the rectifier depending on the speed of movement can be expressed as follows;

$$Kv = KH + a (Vn - VH)$$
 (4)

Here, Kn is the specific resistance of the rectifier at low speeds, N\m;

Vπ- acquired movement speed, m\s;

Vн- low movement speed, m\s;

a- coefficient that takes into account the change in resistivity due to the change in speed.

During the operation of the unit, not all of the effective power generated by the engine is used for useful work [10-17]. The power balance of the soil leveler before planting can be written in the following form:

$$N_e = N_f + N_m + N_n + N_{\delta} + N_{\kappa p} \tag{5}$$

Here Nf = power spent on overcoming friction in mechanisms and gears, kW:

 N_m = the power required to carry the leveler is kW;

 N_n = power used for climbing, kW;

VOLUME 02 ISSUE 11 Pages: 119-126

SJIF IMPACT FACTOR (2021: 5.478) (2022: 5.636)

METADATA IF - 7.356

















 N_6 = power used for bolting, kW;

 N_{KP} = power consumed by the hook of the agricultural machine, kW.

$$Ne = Ne(1 - \eta_{mp}) + \frac{vP_f}{270}\cos\alpha \pm \frac{R}{270}\sin\alpha + Ne\eta_{m\delta} + \frac{KBV}{270}$$
 (6)

Here P_f - resistance to drag (perekativanie), $n\mbox{\ m}$;

 δ – reduction coefficient, %

R- total traction resistance, n\m;

The damping coefficient can be determined by the following expression:

$$\delta = c\mu_1 + d\frac{\mu_1}{V} \tag{7}$$

where µ1 is the coefficient of utilization of the mass of the frame, the ratio of the resistance on the hook corresponding to the leading drive unit of the tractor

$$\frac{P_{\kappa p}}{C_{cu}}$$

s, d are constant coefficients for the area prepared for planting. S=0.2 and d=3 are acceptable.

It is known that the useful work coefficient of the agricultural machine consists of the useful work coefficient of the tractor and aggregated agricultural machine [18-23].

$$\eta_c = \eta_{mp} \cdot \eta_m \tag{8}$$

Here η_c = total useful work coefficient of the unit. $\eta_{\rm Tp}$ = useful tractor efficiency

 $\eta_{\rm T}$ = useful duty ratio of the rectifier.

RESEARCH RESULTS

The useful efficiency of the tractor as a function of the speed of movement is a complex function, which depends on the losses in the power transmission, the chain travel, the movement of the tractor itself, and the losses in the crushing [24-29]. Taking into account the common aspects of useful work coefficients of many aggregates and the complexity of the process of its determination, we will be content with determining the useful work coefficient of the leveler. The total resistance of the land leveling machine before planting can be divided into two groups. The component of the total resistance Pf (power spent on the movement of the rectifier) is a useless resistance or "dead" resistance. The components of the total resistance R and R' coch (the reaction force from the deformation resistance of the soil and the resistance force to the movement of the soil pile) are considered useful resistance. Based on the above, the useful work coefficient of the rectifier can be written as follows:

VOLUME 02 ISSUE 11 Pages: 119-126

SJIF IMPACT FACTOR (2021: 5.478) (2022: 5.636)

METADATA IF - 7.356















$$\eta_m = \frac{R + R_{\kappa \tilde{y}u}}{R_f + R + R_{\kappa \tilde{y}u}} \tag{9}$$

From this, the total useful work coefficient of the aggregate

$$\eta_a = \eta_{mp} \left(\frac{R + R_{\kappa \bar{y}u}}{R_f + R + R_{\kappa \bar{y}u}} \right) \tag{10}$$

Substituting expressions 4, 6, 10 into 2 and solving expressions 1 and 2 together, we get the mathematical expression of the width coverage of the leveler.

$$B = \frac{\theta 270N_{e} \left\{ \varepsilon - \left[1 - \eta_{T} \left(\frac{R + R_{np}}{R_{f} + R + R_{np}} \right) \right] \right\} - R_{f}V}{270N_{e}\eta_{T} \left(\frac{R + R_{np}}{R_{f} + R + R_{np}} \right) \left(C + \frac{d}{V} \right) K_{H} + a(V_{n} - V_{H})}$$

$$C_{cy}$$
(11)

Here θ is the bandwidth utilization factor.

When the leveler works, the two lateral passages should cover each other at a distance of 40-50 cm so that there is no unleveled space between the two lateral passages of the leveler. From this

$$\theta = \frac{[B - (0,4...0,5)]}{B}$$
 if $\theta = 0,93....0,96$

The obtained equation allows to determine the width of the screed by an analytical method, depending on the speed of aggregate movement, physical mechanical properties of the soil, and specific resistance of the screed [30-35].

The resulting equation can be solved much easier by graphoanalytical method. To do this, first, the value of the movement speed is given by the procedure according to equation 11, and the coverage width is determined.




Figure 1. The graph of the change of the leveler coverage width depending on the speed of movement. For class 1-5 tractors. For tractors of class 2-4.

VOLUME 02 ISSUE 11 Pages: 119-126

SJIF IMPACT FACTOR (2021: 5.478) (2022: 5.636)

METADATA IF - 7.356















As can be seen from the graph, the coverage width decreases as the speed of movement increases. But as the power of the tractor increases, the coverage width of the leveler increases dramatically. A super wide straightener is clumsy and inconvenient to use due to its large metal capacity. In order to make full use of the power of the tractor, it is advisable to reduce the width of the leveler and use it at higher speeds. When the working speed of the unit is increased, the work productivity increases, as a result of which the specific metal capacity per treated soil surface decreases. This keeps the soil from compacting [34-35]. The resulting graphical relationship allows to determine the coverage width and speed mode in each size of the leveler and to calculate the theoretical performance.

The nomogram shown in the figure allows determining the optimal movement speed of the unit and the coverage width that provides maximum productivity, depending on the power of the tractor.




Figure 2. Nomogram for determining the coverage width, movement speed and performance of the leveler.

For leveler aggregated with a class 5 tractor. For leveler aggregated with a class 4 tractor.

Conclusion

The top left square of the nomogram shows the variation of maximum productivity as a function of tractor power, the top right square shows the performance of the leveler as a function of the aggregate movement speed, the bottom right

square shows the aggregate coverage width as a function of the movement speed, and the bottom right square shows the specific metal capacity as a function of the coverage width and aggregate mass

REFERENCES

1. Мухамадсадиков, К. Д., & Давронбеков, А. А. (2021). Исследование влияния

VOLUME 02 ISSUE 11 Pages: 119-126

SJIF IMPACT FACTOR (2021: 5.478) (2022: 5.636)

METADATA IF - 7.356















- гидродинамических режимов сферической нижней трубы на процесс теплообмена. Universum: технические науки, (7-1 (88)), 38-41.
- 2. Mukhamadsadikov, K. J., & ugli Ortikaliev, B. S. (2021). Working width and speed of the harrow depending on soil resistivity. Web of Scientist: International Scientific Research Journal, 2(04), 152-158.
- 3. Abdukakhorovich, & A. H., D. (2021). Muhammadsodikov, K. Improving the design of internal plates in columnar apparatus. The American Journal of Engineering and Technology, 3(05), 1-8.
- Мухамадсадиков, К., Ортикалиев, Б., 4. Юсуов, А., & Абдупаттоев, Х. (2021). Ширина захвата и скорости движения выравнивателя зависимости удельного сопротивления почвы. Збірник наукових праць SCIENTIA.
- 5. Baykuzieva, G. A. (2020). Проблемы развития плодоовощной отрасли в ферганской области и пути их решения. Theoretical & Applied Science, (10), 78-82.
- Axunboev, A., Muxamadsodikov, K., & 6. Qoraboev, E. (2021). Drying sludge in the drum. Bargarorlik va yetakchi tadqiqotlar onlayn ilmiy jurnali, 1(5), 149-153...
- Mukhamadsadikov, K., & Ortigaliyev, B. 7. (2022).Constructive Parameters of Earthquake Unit Before Sowing. Eurasian Journal of Engineering and Technology, 9, 55-61.
- Mukhamadsadikov. 8. K. I. (2022).Determination of installation angle and

- height working body of the preseeding leveler. American Journal Of Applied Science And Technology, 2(05), 29-34.
- 9. Axunboev, A., Muxamadsodikov, Djuraev, S., & Musaev, A. (2021). Analysis of the heat exchange device complex in rotary ovens. Barqarorlik va yetakchi tadqiqotlar onlayn ilmiy jurnali, 1(5), 127-132.
- 10. Axunboev, A., & Muxamadsodikov, K. (2021). Drying fine materials in the contact device. Bargarorlik va vetakchi tadqiqotlar onlayn ilmiy jurnali, 1(5), 133-138.
- 11. Adxamovna, B. G. (2021). The procedure for assessing the quality of internal mechanisms of corporate governance in the joint-stock company "Uzbek telecom". South asian journal of marketing & management research, 11(6), 28-32.
- 12. Tojiyev, R., Rajabova, N., Ortigaliyev, B., & Abduolimova, M. (2021). Destruction of soil crust by impulse impact of shock wave and gas-dynamic flow of detonation products. Innovative Technologica: Methodical Research Journal, 2(11), 106-115.
- Ортиқалиев, Б. С., & Тожиев, Р. Ж. 13. (2019). Сито-бурат СМ-237Арусумли оловбардош ашёсини ғишт XOM саралаш машинисини иш режмларини тахлили.".
- **14.** Tojiyev, R., Ortigaliyev, B., Toʻlashev, O., & Sobirov. (2022).Alumosilikat X. olovbardosh *'ishtning* xossalariga g

VOLUME 02 ISSUE 11 Pages: 119-126

SJIF IMPACT FACTOR (2021: 5.478) (2022: 5.636)

METADATA IF - 7.356















- saralash jarayonini ta'siri tahlili. Scientific progress, 3(4), 1271-1276...
- **15**. Tojivev, R. I., Ortigaliyev, B. S. O. G. L., & Abdurayimov, A. A. O. G. L. (2021). Saralash mashinalarining qiyosiy tahlili. Science and Education, 2(11), 359-367.
- 16. Tojiyev, R., Ortigaliyev, B., Abdupattoyev, X., & G'ulomov, I. (2021). Production of refractory bricks in industrial enterprises and sorting of their raw materials. Матеріали конференцій МЦНД.
- Mukhamadsadikov, K., Ortigaliyev, B., **17.** Olimova, D., & Isomiddinova, D. (2021). Mathematical analysis of determining the parameters of the working part of the planting plant before planting. Scientific progress, 2(7), 699-708.
- 18. Khoshimov, A., Abdulazizov, A., Alizafarov, B., Husanboyev, M., Xalilov, I., Mo'vdinov, A., & Ortigaliyev, B. (2022). Extraction of caprolactam in two stages in a multiplestage barbotation extractor. Conferencea, 53-62.
- **19**. Rasuljon, T., Isomiddinov, A., Ortigaliyev, B., & Khursanov, B. Z. (2022). Influence of previous mechanical treatments material grinding. International Journal of Advance Scientific Research, 2(11), 35-43.
- 20. Tojiev, R. J., Ortikaliev, B. S., Sobirov, K., & Tolashev, O. (2022). Study of the mechanical and physico-chemical process of the metal structure of the sorting machine. Conferencea, 44-51.
- 21. Ergashev, N., & Halilov, I. (2021). Experimental determination length of liquid film in dusty gas cleaner. Innovative

- Technologica: Methodical Research Journal, 2(10), 29-33.
- 22. Karimov, I., & Halilov, I. (2021). Modernization of the main working shovels of the construction mixing device.
- 23. Ikromali, K., & Ismoiljon, H. (2021). Hydrodynamics of Absorption Bubbling Apparatus. Бюллетень науки практики, 7(11), 210-219.
- Ergashev, N. A., Davronbekov, A. A., 24. Khalilov, I. L. C., & Sulaymonov, A. M. (2021). Hydraulic resistance of dust collector with direct-vortex contact elements. Scientific progress, 2(8), 88-99.
- Ergashev, N., Ismoil, K., & Baxtior, M. 25. (2022). Experimental determination of hydraulic resistance of wet method dushanger and gas cleaner. American Iournal Of Applied Science And Technology, 2(05), 45-50.
- Karimov, I., Xalilov, I., Nurmatov, S., & 26. Qodirov, A. (2021). Barbotage absorbation apparatus. Bargarorlik va vetakchi tadqiqotlar onlayn ilmiy jurnali, 1(5), 35-41.
- 27. Ализафаров, Б. М. (2020). Ecological drying of fine dispersed materials in a contact dryer. Экономика и социум, (11), 433-437.
- 28. Тожиев, Р. Ж., Садуллаев, Х. Сулаймонов, А., & Герасимов, М. Д. (2019). Напряженное состояние вала с поперечным отверстием при изгиба совмесстном действии И In кручения. Энергоресурсосберегающие технологии

VOLUME 02 ISSUE 11 Pages: 119-126

SJIF IMPACT FACTOR (2021: 5.478) (2022: 5.636)

METADATA IF - 7.356

















- оборудование дорожной В И строительной отраслях (рр. 273-281).
- 29. Tojivev, R., Isomidinov, A., & Alizafarov, B. (2021). Strength and fatigue of multilayer conveyor belts under cyclic loads. Turkish Journal of Computer and Mathematics Education, 12(7), 2050-2068.
- 30. Tojiev, R., Alizafarov, B., & Muydinov, A. (2022). Theoretical analysis of increasing conveyor tape endurance. Innovative technologica: methodical research journal, 3(06), 167-171.
- Rasuljon, T., & Bekzod, A. (2022). 31. Theoretical research of stress in rubberfabric convevor belts. Universum: технические науки, (4-12 (97)), 5-16.
- Axunboev, A., Alizafarov, B., Musaev, A., & **32**. Karimov, A. (2021). Analysis of the state of the problem of ensuring the operation of the rotating units. Bargarorlik va yetakchi tadqiqotlar onlayn ilmiy jurnali, 1(5), 122-126.
- 33. Obidjon o'g'li, X. A. (2022). Factors affecting the working process of industrial dust gases cleaning apparatus. Yosh Tadqiqotchi Jurnali, 1(6), 7-13.
- 34. Axmadjonovich, E. N., Obidjon o'g'li, X. A., & Abduqayum o'g'li, A. M. (2022). Industrial application of dust equipment in the industrial wet method with contact elements and experimental determination of its efficiency. American Journal of Applied Science and Technology, 2(06), 47-54..
- Axmadjonovich, E. N., Abdugaxxor o'g'li, A. 35. A., & Mahmudjon o'g'li, I. M. (2022).

Determination of Efficiency for Cleaning Ouartz Sand and Dolomite Dust in A Wet Method Dust Cleaning Machine. Eurasian Research Bulletin, 9, 39-43.

